


备注：  
 1. 内模都用HDPE料，分线胶外模用TPE75A黑色胶料。  
 2. 插头MIC为粉红色(701C)；SPK为浅橙色(157C)。  
 3. 插头外模不得有缩水、杂色、冲胶、露线等现象。  
 4. 插头表面不得有氧化、压伤、剥伤、变形等现象。



ITEM	PART NO:	DESCRIPTION	QTY
1	立体头	3.5MM镀镍立体头(4.5圆盘L=27.0MM)	2
2	电线	2.5mmTPE黑色五芯(10/0.08mm*3C)+[(10/0.08mm*1C包中被)+包22/0.08mm] L=2.05M	1
3	电线	2.0mmTPE黑色三芯(10/0.08mm*3C)*1F L=0.17M	1
4	电线	2.0mmTPE黑色二芯(10/0.08mm*1C包中被)包27/0.08cm] *1F L=0.17M	1
5	PCB	5.7*6*1mm双面接线PCB(五芯线)料号(20-41800600-00)	1

# 立扬有限公司

TITLE		3.5镀镍立体头耳麦2.15M半成品线(01-G0462-9001RS)			
MODEL	MH78-GMX01	PART NO:	1863024140	DRAWING NO:	1863-50656
DRAWN BY	王闯	SCALE	1:1	REV.	A
APPROVED BY		DATE	09.04.27	UNITS	mm